

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Horizont Zinkoxid-Salbenspray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Pet care

1.3. Details of the supplier of the safety data sheet

Company name:	Friedrich Huber aeronova GmbH & Co.KG	
Street:	Sobrigauer Weg 4	
Place:	D-01257 Dresden	
Telephone:	0049-(0)351-27046-0	Telefax: 0049-(0)351-2704616
e-mail:	info@aeronova.de	
e-mail (Contact person):	labor@aeronova.de	
Internet:	www.aeronova.de	
Responsible Department:	laboratory	

1.4. Emergency telephone number: 0049-(0)351-27046-0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Signal word: Danger

Pictograms:





Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 2 of 15

Hazard statements

- | | |
|------|--|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: May burst if heated. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements

- | | |
|-----------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P302+P352 | IF ON SKIN: Wash with plenty of water. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 3 of 15

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
106-97-8	butane			25 - < 30 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
74-98-6	propane			12.5 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
8042-47-5	Paraffinum liquidum			10 - < 12.5 %
	232-455-8		01-2119487078-27	
	Asp. Tox. 1; H304			
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			10 - < 12.5 %
	926-605-8		01-2119486291-36	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411			
1314-13-2	zinc oxide			10 - < 12.5 %
	215-222-5		01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			5 - < 10 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			5 - < 10 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
	Hydrocarbons, C6, isoalkanes, <5% n-hexane			5 - < 10 %
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
110-54-3	n-hexane			0.5 - < 1 %
	203-777-6	601-037-00-0	01-2119480412-44	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411			
97-59-6	5-Ureido-Hydantoine			0.1 - < 0.5 %
	202-592-8		01-2119953242-43	
110-82-7	cyclohexane			0.1 - < 0.5 %
	203-806-2		01-2119463273-41	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1; H225 H315 H336 H304 H400 H410			

Full text of H and EUH statements: see section 16.

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 4 of 15

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

High power water jet

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 5 of 15

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Pet care

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
110-54-3	n-Hexane	20	72		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 6 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day

8.2. Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Wear eye/face protection. Suitable eye protection: Eye glasses with side protection DIN EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. DIN EN 374

Suitable material: NBR (Nitrile rubber) (0,35 mm)

Breakthrough time (maximum wearing time): ≥ 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Usually no personal respiratory protection necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: white
Odour: like: Gasoline

Test method

pH-Value: not applicable

Changes in the physical state

Melting point: not applicable

Initial boiling point and boiling range: < -20 °C

Flash point: < -20 °C

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 7 of 15

Sustaining combustion:

No data available

Flammability

Solid:

not applicable

Gas:

not applicable

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:

0,6 vol. %

Upper explosion limits:

8,4 vol. %

Ignition temperature:

> 200 °C

Auto-ignition temperature

Solid:

not applicable

Gas:

not applicable

Decomposition temperature:

not determined

Oxidizing properties

not determined

Vapour pressure:

not determined

Density (at 20 °C):

0,74 g/cm³ calculated.

Water solubility:

practically insoluble

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient:

not determined

Viscosity / kinematic:

not applicable

Vapour density:

not determined

Evaporation rate:

not determined

Solvent content:

not determined

9.2. Other information

Solid content:

not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 8 of 15

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
8042-47-5	Paraffinum liquidum			
	oral	LD50 > 5000 mg/kg	Rat	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	OECD Guideline 402
	inhalative (4 h) vapour	LC50 > 5000 mg/l	Rat	OECD 403
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			
	oral	LD50 >5000 mg/kg	Rat	OECD 401
	dermal	LD50 >2000 mg/kg	Rabbit	OECD 402
1314-13-2	zinc oxide			
	oral	LD50 > 5000 mg/kg	Mouse	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	OECD Guideline 402
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
	oral	LD50 >5840 mg/kg	Rat	
	dermal	LD50 >2920 mg/kg	Rat	
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
	oral	LD50 > 5000 mg/kg	Rat	
	dermal	LD50 > 2000 mg/kg	Rat	
	inhalative (4 h) vapour	LC50 (> 20) mg/l	Rat	
	Hydrocarbons, C6, isoalkanes, <5% n-hexane			
	oral	LD50 > 5000 mg/kg	Rat	OECD 401
	dermal	LD50 > 3000 mg/kg	Rat	OECD 402
	inhalative (4 h) vapour	LC50 > 20 mg/l	Rat	OECD 403
110-54-3	n-hexane			
	dermal	LD50 > 2000 mg/kg	Rabbit	ECHA
	inhalative (4 h) gas	LC50 > 31,86 ppm	Rat	IUCLID
97-59-6	5-Ureido-Hydantoine			
	oral	LD50 >5000 mg/kg	Rat	CIT
	dermal	LD50 >5000 mg/kg	Rat	

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.



Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 9 of 15

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane), (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane), (Hydrocarbons, C6, isoalkanes, <5% n-hexane), (n-hexane), (cyclohexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 10 of 15

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
74-98-6	propane				
	Acute fish toxicity	LC50 27,98 mg/l	96 h	Fish, no other information	ECHA
	Acute algae toxicity	ErC50 7,71 mg/l	96 h	Green algae	ECHA
8042-47-5	Paraffinum liquidum				
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203
	Acute algae toxicity	ErC50 100 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna (Big water flea)	
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane				
	Acute fish toxicity	LC50 12 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203
	Acute algae toxicity	ErC50 7,276 mg/l	72 h	Selenastrum capricornutum	ECHA
	Acute crustacea toxicity	EC50 3 mg/l	48 h	Daphnia magna	OECD Guideline 202
	Fish toxicity	NOEC 2,187 mg/l	28 d	Oncorhynchus mykiss	ECHA
	Crustacea toxicity	NOEC 3,818 mg/l	21 d	Daphnia magna	ECHA
1314-13-2	zinc oxide				
	Acute fish toxicity	LC50 4,92 mg/l	96 h	Danio rerio	ECHA
	Acute crustacea toxicity	EC50 7,5 mg/l	48 h	Daphnia magna	OECD Guideline 202
	Algae toxicity	NOEC (0,08) mg/l	4 d	Dunaliella tertiolecta	IRSA-CNR
	Crustacea toxicity	NOEC (0,058) mg/l	21 d	Daphnia magna	OECD Guideline 211
	Acute bacteria toxicity	(5,2 mg/l)	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics				
	Acute fish toxicity	LC50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Selenastrum capricornutum	OECD Guideline 201
	Acute crustacea toxicity	EC50 3 mg/l	48 h	Daphnia magna	OECD Guideline 202
	Fish toxicity	NOEC 1,534 mg/l	28 d	Oncorhynchus mykiss	ECHA
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	OECD Guideline 211
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	Acute fish toxicity	LC50 11,4 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203
	Acute algae toxicity	ErC50 (10 - 30) mg/l	72 h	Raphidocelis subcapitata	OECD Guideline 201
	Acute crustacea toxicity	EC50 3 mg/l	48 h	Daphnia magna	OECD Guideline 202
	Fish toxicity	NOEC (2,045) mg/l	28 d	Oncorhynchus mykiss	ECHA
	Crustacea toxicity	NOEC (1) mg/l	21 d	Daphnia magna	OECD Guideline 211
	Hydrocarbons, C6, isoalkanes, <5% n-hexane				
	Acute fish toxicity	LC50 18,27 mg/l	96 h	Oncorhynchus mykiss	ECHA
	Acute algae toxicity	ErC50 13,56 mg/l	72 h	Selenastrum capricornutum	ECHA
	Acute crustacea toxicity	EC50 31,9 mg/l	48 h	Daphnia magna	ECHA
	Fish toxicity	NOEC 4,089 mg/l	28 d	Oncorhynchus mykiss	ECHA
	Crustacea toxicity	NOEC 7,138 mg/l	21 d	Daphnia magna	ECHA

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 11 of 15

110-54-3	n-hexane					
	Acute fish toxicity	LC50	12,51 mg/l	96 h	Oncorhynchus mykiss	ECHA
	Acute algae toxicity	ErC50	9,285 mg/l	72 h	Selenastrum capricornutum	ECHA
	Acute crustacea toxicity	EC50	21,85 mg/l	48 h	Daphnia magna	ECHA
	Fish toxicity	NOEC	(2,8) mg/l	28 d	Oncorhynchus mykiss	ECHA
	Crustacea toxicity	NOEC	(4,888) mg/l	21 d	Daphnia magna	ECHA
97-59-6	5-Ureido-Hydantoine					
	Acute fish toxicity	LC50	>5000 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50	>100 mg/l	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50	>100 mg/l	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity		(>10 mg/l)	3 h	Pseudomonas putida	IRCHA
110-82-7	cyclohexane					
	Acute fish toxicity	LC50	4,53 mg/l	96 h	Pimephales promelas	OECD Guideline 203
	Acute algae toxicity	ErC50	3,4 mg/l	72 h	Selenastrum capricornutum	OECD Guideline 201
	Acute crustacea toxicity	EC50	0,9 mg/l	48 h	Daphnia magna	OECD Guideline 202

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			
	Biodegradation	98%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
	Biodegradation	98%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
	Biodegradation	81%	28	
	Readily biodegradable (according to OECD criteria).			
97-59-6	5-Ureido-Hydantoine			
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	76	29	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
110-54-3	n-hexane	4
97-59-6	5-Ureido-Hydantoine	-2,26

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 12 of 15

BCF

CAS No	Chemical name	BCF	Species	Source
1314-13-2	zinc oxide	28960	Palaemon elegans	ECHA
	Hydrocarbons, C6, isoalkanes, <5% n-hexane	501,187	Pimephales promelas	ECHA
110-54-3	n-hexane	501,187	Pimephales promelas	ECHA
110-82-7	cyclohexane	242		ECHA

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 13 of 15

Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203

Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 14 of 15

IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): 68,871 % (509,647 g/l)

2004/42/EC (VOC): 68,871 % (509,647 g/l)

Additional information

To follow: 850/2004/EC, 1107/2009/EC, 649/2012/EC Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,7,9.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: May burst if heated.



Horizont Zinkoxid-Salbenspray

Print date: 11.08.2016

Page 15 of 15

H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)